



- (1) Jacket Color : Gray(RAL7035)
- (2) Wiring : T568B

Item no.	length	tolerance mm
21.15.0874	20M	+70 -30
21.15.0876	30M	+70 -30
21.15.0877	50M	+70 -30
21.15.0878	70M	+70 -30
21.15.0879	90M	+70 -30

Specification :

Material :

1. RJ45 Plug : for 23AWG solid wire.
 - 1-1. Housing : Polycarbonate, Blue color.
 - 1-2. Contact finished : Min. 50 micro-inch gold plating over min. 50 micro-inch nickel plating on surface contact area.
 - 1-3. Contact material : Phosphor bronze.
 - 1-4. Shield : Zinc Alloy with nickel plating.
2. SR : PC material.
3. Cable :
 - 3-1. Cable structure : S/FTP, 4 twisted pair, OD 7.3±0.2mm
 - 3-2. Jacket : LSZH material.
 - 3-3. Conductors : 23AWG solid.
 - 3-4. Insulation : Foam PE
 - 3-5. Shield : Aluminum foil and braid with copper clad with steel material.
4. Bend radius: Min.29mm (4x of cable OD)

item no	21.15.0874	21.15.0876	21.15.0877	21.15.0878	21.15.0879
Desc	ROLINE CAT.6A S/FTP Patch Cord, LSOH, Gray				
GENERAL TOLERANCE OF DIMENSIONS x.xxx ±0.005 x.xx ±0.05 x.x ±0.1	DRAWING	27.JUL.2022	SP	SECOMP	
	CHECK	27.JUL.2022	CMD		
	APPROVAL	27.JUL.2022	YUAN		
	DATE		NAME		
SCALE	1/1 (A4)	UNIT	mm		
		DRAWING NO.			
		DRAWING CLASSIFICATION			