



ITEM NO.	LENGTH
11. 99. 8809B	800±20mm
11. 99. 8819B	1800±30mm
11. 99. 8831B	3000±50mm
11. 99. 8841B	4500±100mm

MATERIAL LIST:

④	OUTER MOLD	Shore 88A PVC Color: White	2	
③	USB B TYPE	USB B /M Type, The Pin Gold Plating 3U", the shell for Nickel Plating	1	
②	USB A TYPE	USB A /M Type, The Pin Gold Plating 3U", the shell for Nickel Plating	1	
①	CABLE	USB 2.0 28AWG (BC*1P)+28AWG (BC*2C)+AB AL-MG JACKET:PVC/white OD: 3.8±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

NEW

2018-12-05

A

BY

CHK

REVISION RECORD MODIFICATIONS

DATE

REV.

NOTE:

1. Electrical test:

(1).100% open short & miss wire test;

(2).Insulation resistance:DC 300V 10M Ω ;

(3).Contactor resistance:3Ω Max;

(4).Dielectric strength:100V AC/Minute,1mA.

2. RoHS 2.0 & REACH compliant

3. PRINTING:USB 2.0 CABLE, 28AWG×1P+28AWG×2C

DESC. VALUE USB 2.0 Cable Type AM-BM,white

SECOMP