



Features:

1. Compatible with USB3.2 Gen 1, USB2.0, USB1.1
2. Data Transfer rates up to 5.0 Gbit/s
3. Active USB extender cable ensures signal transmission stability
4. Hot-swappable
5. Supports Windows 2000/XP/Vista/7/8/8.1/10
6. Max supported voltage and current :5V/0.9A

Shell

				TOLERANCE			
				INCHES	M/M		
				.X	.015		
				.XX	.010	.10	
				.XXX	.005	.05	
5	CEU3E0101Shell 2(ABS)	1	pcs	DRAWN BY		CUSTOMER P/N : 12.04.1096	
4	CEU3E0101 Shell 1(ABS)	1	pcs	CHECK BY		SCALE	NONE
3	CEU3E0101 (USB 3.2 Gen1 cable extender) PCBA~USB A/F PIN G/F Shell Nickel Plated	1	pcs	APPD BY		UNIT	MM
2	USB 3.2 Gen1 A(M) 9P PIN Gold 5u with Shell Nickel Plated	1	pcs			DATE	22/11/30
1	UL2725[26AWG(7/0.16TC)+EAM]*2P+[28AWG(7/0.127TC)+A]*1P+22AWG(7/0.254TC)*2C+AEB(16/6/0.12TC 65%AL)OD:6.0mm~Black	5	M			DRAWING NO.: CEU3E0101-A179	
NO	DESCRIPTION	Q'TY	UNIT			REV. A0 1/1	