



DIGITUS Bidirectional Fast Ethernet Media Converter, RJ45 / SC

DN-82022 4016032293149



The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100Base-TX to 100Base-FX
- Connectors: 1x RJ45, 1x SC Simplex
- Distance up to 20km
- Wavelength: Tx 1310nm / Rx 1550nm
- Singlemode Single Fiber
- Automatic Cable detection - Auto MDI / MDI-X function
- Auto-Negotiation of Full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Link Fault Pass Through (LFP) Function for easier Network Maintenance
- Suitable for 9/125µm Fiber Cables
- Transmission Power: Minimum -15 dBm, Maximum -8 dBm
- Sensitivity Receiving Power: Minimum -36 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet
- 128kB Data Buffer
- Operating Temperature: 0 to 55°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC
- Max. Current: 800mA
- Power Consumption: 2.5W
- Suitable Converter for Opposite Side: DN-82023



Package Content

- Media Converter
- Quick Installation Guide
- Power Adapter



DIGITUS Bidirectional Fast Ethernet Media Converter, RJ45 / SC

DN-82022 4016032293149



→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	9,00	30,00	27,00	55,00	44550,00
Packaging Unit Inside	1	0,45	5,50	13,00	24,00	1716,00
Packaging Unit Single	1	0,45	5,50	13,00	24,00	1716,00
Net single without Packaging	1	0,00	2,60	7,00	9,50	172,90

→ Packaging type



Country of origin: China