


# ROLINE USB 3.2 Gen 2x2 Cable, PD (Power Delivery) 20V5A, with Emark, C-C, M/M, black, 1.5 m

<b>Product No.</b>	11.02.9072
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	11.02.9072
<b>EAN (single piece)</b>	7630049619265



**USB 3.2 Gen 2x2 cable with up to 20 Gbit/s speed mode that uses a more efficient data encoding and will deliver more than twice the effective data through-put performance of existing, fully backward compatible USB connectors and cables.**

- High quality USB 3.1 / USB 3.2 Gen 2x2 cable with improved shielding
- With the reversible Type C connectors at both ends
- Gold-plated contacts for low wear at high plugging cycles
- Suitable for data transfer rates of up to 20 Gbit/s
- Supports USB Power Delivery to 20V / 5A

Note: According to the current specifications of USB.org we have adapted the technical data of our USB 3 products. The new designation for the already known USB specifications has been changed to USB 3.2 Gen 1 (formerly USB 3.0 / USB 3.1 Gen 1) and USB 3.2 Gen 2 (formerly USB 3.1 / USB 3.1 Gen 2).

## Technical specifications

Manufacturer	ROLINE
Product group	Cable
Product type	USB 3.2 Cable
Colour	black
Length	1.5 m
Transfer quality	USB 3.2 Gen 2x2 SuperSpeed 20 Gbit/s

Connection ports	USB Type C (USB-C) Male / USB Type C (USB-C) Male
Side 1 Connector Type	USB Type C (USB-C)
Side 1 Connector Gender	Male
Side 2 Connector Type	USB Type C (USB-C)
Side 2 Connector Gender	Male
Area of application	External
Supported charging technology	USB-PD - USB Power Delivery
Cable shielding	Screened
Hand locking screws	No
Weight	63.1 g
Height of packaging (single piece)	2 mm
Width of packaging (single piece)	210 mm
Depth of packaging (single piece)	310 mm
Package weight (single piece)	0.075 kg