

DATASHEET

19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035



General data

19" Wall housing 1-part, type Flat Pack
 Steel sheet housing screwable, not pre-assembled
 Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
 Front door lockable, Door opening angle 120°
 Door stop easy changeable (right/left)
 Sidewalls not detachable
 Roof prepared for mounting of 2 x single fans
 Roof and bottom with cable entry 145 x 70 mm
 Inside 2 x 19" profile rails, depth-adjustable, with lateral opening for cable routing
 Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
 Width 535 mm, depth 450 / 600 mm
 Max. load 80 kg (static, equally distributed)
 Protection degree IP20
 Incl. key
 Delivery unassembled in 1 carton with handle

Allgemeine Daten

Modular spacing	482.6 mm (19 inch)
With front door	True

This datasheet was created automatically on 10-02-2024 . Technical changes reserved.



DATASHEET

19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035

Type of ventilation	Passive
Demountable	True
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Mounting level	Front side
With sidewall	True
Model	With permanent frame
With earthing	True
Number of doors	1
Material	steel
Degree of protection	IP20
Type of profile rail	L-shaped

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
WGB-1906GR.45	19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035	grey	450 mm	304 mm	80 kg	6 U	535 mm	7035
WGB-1909GR.45	19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035	grey	450 mm	437 mm	80 kg	9 U	535 mm	7035
WGB-1912GR.45	19" 12U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035	grey	450 mm	571 mm	80 kg	12 U	535 mm	7035
WGB-1915GR.45	19" 15U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035	grey	450 mm	707 mm	80 kg	15 U	535 mm	7035

This datasheet was created automatically on 10-02-2024 . Technical changes reserved.

