



PIN OUT

P1 (USB/TYPER C)		P2 (DP/M-PCBA)	
ALUMINIUM { GND	DRAIN	GND	GND
A3	BLUE	A3	A3
A2	WHITE	A2	A2
ALUMINIUM { GND	DRAIN	GND	GND
B10	GREEN	B10	B10
B11	WHITE	B11	B11
ALUMINIUM { GND	DRAIN	GND	GND
B3	RED	B3	B3
B2	WHITE	B2	B2
ALUMINIUM { GND	DRAIN	GND	GND
A10	BROWN	A10	A10
A11	WHITE	A11	A11
A8	GREY	A8	A8
B5	YELLOW	B5	B5
{ A7	GREEN	A7	A7
A6	WHITE	A6	A6
B8	PURPLE	B8	B8
A5	ORANGE	A5	A5
PWR	RED	PWR	PWR
SHELL	BRAID	SHELL	SHELL

NOTE:

100% DELL MAC BOOK HDTV TEST 3840×2160@60Hz
 Operating Temperature: 0°C~45°C
 Storage Temperature: -20°C~ 70°C
 USB Type C male input
 Display port 1.2v male output
 ROHS 2.0 and Reach compliant

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
⑥	DUST CAP	LD-PE	1	
⑤	HOUSING	ABS Black	2	
④	INNER MOLD	LD-PE	2	
③	DP FEMALE	DP 20P A/F , BLACK INSULATION, , THE PIN GOLD PLATED , THE SHELL FOR GOLD PLATED+PCB	1	
②	USB C TYPE	USB C /M Solder Type, Black PBT Insulation, The Pin Gold Plating, the shell for GOLD Plating	1	
①	CABLE	USB3.1-C CABLE (32AWG TC*1P+D+AL+HM) *4P+32AWG TC*1P+32AWG TC*4C+24AWG TC*2C+AB PVC/Black Jacket OD:4.5±0.2	1	

ITEM NO.	length
11.99.5846	2000±30mm
11.99.5845	1000±20mm

ITEM NO.	DESC.
11.99.5846	VALUE Adaptercable USB Type C-DP, M/M, 2m
11.99.5845	VALUE Adaptercable USB Type C-DP, M/M, 1m

NEW		2017.10.12	A
BY	CHK	REVISION RECORD MODIFICATIONS	REV.

