


VALUE UTP Patch Cord Cat.6A (Class EA), white, 1.5 m

| | |
|---------------------------|---------------|
| Product No. | 21.99.1486 |
| Manufacturer | VALUE |
| Manufacturer No. | 21.99.1486 |
| EAN (single piece) | 7611990142415 |



- The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz
- Patch cable for networking connections between devices
- Prepared shielded Twisted Pair cable (PiMF) with RJ-45 connectors on both ends.
- Durable due to moulded kink protection.
- Flexible cable, suitable for narrow bending.
- Impedance: 100 Ohm
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard.
- Construction: 8 lines, pairs shielded with aluminium foil, complete shielding in tinned copper braid

For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a UTP Cable, Solid Wire, 300 m: 21.99.1681

Flush Mount Wall Jack for Keystones: 25.16.8579

Surface Wall Mount Frame: 25.16.8484

VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366

19" Keystone Patch Panel: 26.11.0358 / 26.11.0359

VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0875

Technical specifications

| | |
|------------------------------------|--------------------|
| Manufacturer | VALUE |
| Product group | Twisted Pair Cable |
| Product type | UTP Patch Cables |
| Colour | white |
| Length | 1.5 m |
| Shield type | UTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | No |
| Cable LSOH | No |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| Weight | 59 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 150 mm |
| Depth of packaging (single piece) | 150 mm |

Package weight (single piece) 0.073 kg