

ROLINE Outdoor S/FTP Patch Cord Cat.6A / Class EA, Stranded, TPE, LSOH, black, 3 m

| | |
|---------------------------|---------------|
| Product No. | 21.15.0753 |
| Manufacturer | ROLINE |
| Manufacturer No. | 21.15.0753 |
| EAN (single piece) | 7630049627482 |

roline
Designed for Professionals



Cat. 6A
Class EA

S/FTP

LSOH

Assembled double shielded (PiMF) twisted pair cable category 6A with shielded RJ-45 connectors on both sides. For outdoor use (cable routing), e.g. for connecting an IP camera.

Patch cord for networking connections between devices in combination with outdoor application (e.g. connection to outdoor surveillance cameras)

- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Suitable for PoE applications and multimedia applications where the extension is working over TP
- High quality plugs with gold plated contacts
- UV - resistant (Ultraviolet resistance - ability of the material to withstand the degradation that can be caused by exposure to ultraviolet light)
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire, complete braid shielding, pairs shielded with aluminium foil

REMARK: NOT suitable for underground installation / application

Technical specifications

| | |
|----------------------------------|--------------------|
| Manufacturer | ROLINE |
| Product group | Twisted Pair Cable |
| Product type | S/FTP Patchcord |
| Colour | black |
| Length | 3 m |
| Shield type | PiMF |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 26 |
| Conductor type | Wire |
| Crossed | no |
| Bend radius | Min. 25mm |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| External cable diameter | 6.0 +/-0.2mm |
| Cable LSOH | yes |
| Material (external cable mantle) | TPE |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -40 °C |
| Operating temperature max. | 60 °C |

| | |
|-----------------------------|--------|
| Storage temperature min. | -40 °C |
|-----------------------------|--------|

| | |
|-----------------------------|-------|
| Storage temperature max. | 75 °C |
|-----------------------------|-------|

| | |
|--------|------|
| Weight | 91 g |
|--------|------|

| | |
|---------------------------------------|-------|
| Height of packaging (single piece) | 10 mm |
|---------------------------------------|-------|

| | |
|--------------------------------------|--------|
| Width of packaging (single piece) | 120 mm |
|--------------------------------------|--------|

| | |
|--------------------------------------|--------|
| Depth of packaging (single piece) | 160 mm |
|--------------------------------------|--------|

| | |
|----------------------------------|---------|
| Package weight (single piece) | 0.11 kg |
|----------------------------------|---------|