VALUE S/FTP Patch Cord Cat.6A (Class EA), blue, 0.3

m

| Product No. Manufacturer Manufacturer No. EAN (single piece) | 21.99.1954 VALUE 21.99.1954 7630049612402 | Value |
|---|---|-------|
| | UTP = U/UTP FTP = F/UTP UTP = U/UTP FTP = F/UTP SFTP (Cat.Be) SFTP (Cat.B) SFTP (Cat.Be) SFTP (Cat.B) SFTP (PMF) SFTP (PMF) Creent: sluminium oled fuil / Red: timed copper braid | |
| Cat.6A | | |

The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz. Patch cable for networking connections between devices. Prepared shielded Twisted Pair cable (PiMF) with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Impedance: 100 Ohm. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 8 lines, pairs shielded with aluminium foil, complete braided shielding.

For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a S/FTP Cable, Solid Wire, 100 m: 21.99.0881.
Flush Mount Wall Jack for Keystones: 25.16.8579.
Surface Wall Mount Frame: 25.16.8484.
VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366.
19" Keystone Patch Panel: 26.11.0359.
VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0865.

LSOH

57FTP

Class EA

| Technical specifications | |
|--------------------------|-------|
| Manufacturer | VALUE |

| Product group | Twisted Pair Cable |
|---------------------------------------|--------------------|
| Product type | S/FTP Patchcord |
| Colour | blue |
| Length | 0.3 m |
| Shield type | SFTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | Νο |
| Colour (Spout) | blue |
| Cable LSOH | Yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Weight | 17.5 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 140 mm |
| Depth of packaging (single piece) | 150 mm |
| Package weight (single piece) | 0.025 kg |
| | |