

DATASHEET

19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005



General data

19" Wall housing 1-part, type Flat Pack
 Steel sheet housing screwable, not pre-assembled
 Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
 Front door lockable, Door opening angle 120°
 Door stop easy changeable (right/left)
 Sidewalls not detachable
 Roof prepared for mounting of 2 x single fans
 Roof and bottom with cable entry 145 x 70 mm
 Inside 2 x 19" profile rails, depth-adjustable, with lateral opening for cable routing
 Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
 Width 535 mm, depth 450 / 600 mm
 Max. load 80 kg (static, equally distributed)
 Protection degree IP20
 Incl. key
 Delivery unassembled in 1 carton with handle

Allgemeine Daten

| | |
|-----------------|--------------------|
| Modular spacing | 482.6 mm (19 inch) |
| With front door | True |

This datasheet was created automatically on 10-02-2024 . Technical changes reserved.



DATASHEET

19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005

| | |
|----------------------|----------------------|
| Type of ventilation | Passive |
| Demountable | True |
| Surface finishing | powder coating |
| Number of cartons | 1 |
| With roof plate | True |
| Mounting level | Front side |
| With sidewall | True |
| Model | With permanent frame |
| With earthing | True |
| Number of doors | 1 |
| Material | steel |
| Degree of protection | IP20 |
| Type of profile rail | L-shaped |

Available variants

| ArtNr. | Bezeichnung | Colour | Depth | Height | Max. Load | Number of height units | Width | RAL-Nummer |
|---------------|--|--------|--------|--------|-----------|------------------------|--------|------------|
| WGB-1906TS.45 | 19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005 | black | 450 mm | 304 mm | 80 kg | 6 U | 535 mm | 9005 |
| WGB-1909TS.45 | 19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005 | black | 450 mm | 437 mm | 80 kg | 9 U | 535 mm | 9005 |
| WGB-1912TS.45 | 19" 12U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005 | black | 450 mm | 571 mm | 80 kg | 12 U | 535 mm | 9005 |
| WGB-1915TS.45 | 19" 15U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL9005 | black | 450 mm | 707 mm | 80 kg | 15 U | 535 mm | 9005 |

This datasheet was created automatically on 10-02-2024 . Technical changes reserved.

