

ROLINE Keystone Jack, Cat.8 (Class I), RJ-45, STP, tool-free, silver, silver

Product No.	26.11.0381
Manufacturer	ROLINE
Manufacturer No.	26.11.0381
EAN (single piece)	7630049611016



Cat.8 Keystones are ideal for use in 10 Gigabit Ethernet networks

Keystone in proven ROLINE quality!

- The ROLINE Cat.8 Keystones are ideal for use in Gigabit Ethernet networks
- Support data transfer rates up to 10/25/40 Gbit/s with a bandwidth of 2000 MHz
- Connect the cable to the Keystones via LSA connections without special tools - place the cable ends simply into the guides (with color coding), close and compress the module - the connection is ready for use
- The Keystone modules can be "latched" into a 19" module support rack, which is optionally available in black (26.11.00360) or light gray (26.11.0359).
- Cable entrance diameter range: 5.5mm - 9.0mm
- Insulation diameter range: 0.95mm - 1.62mm
- Solid and Stranded conductor: 22AWG - 24AWG for Cat.8 type
- Wire coded scheme: EIA/TIA 568

For a structured cabling system we recommend to use the following components:

21.15.0005 ROLINE S/FTP Cable Cat.8, Solid Wire, LSOH, 24 m; 21.15.1853 ROLINE S/FTP Patch Cord Cat.8, solid, LSOH, yellow, 3 m; 21.15.1863 ROLINE S/FTP Patch Cord Cat.8, stranded, LSOH, yellow, 3 m; 26.11.0381 ROLINE C8 Shield RJ45 Keystone, toolless. The accredited German laboratory GHMT has tested and certified this product combination, in a 2 Connector Channel (30m), Copper, Class I up to 2 GHz; certificate no. c7794a-23.

Technical specifications

Manufacturer	ROLINE
--------------	--------

Product group	Connection technology TP
Product type	RJ45 Keystone Jack
Colour	silver
Shield type	Screened
Transfer quality	Cat8.1 / Class I
Assignment	EIA/TIA 568A & 568B
Connection direction	Straight
Height	21 mm
Width	12 mm
Depth	38 mm
Weight	29.4 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	20 mm
Depth of packaging (single piece)	60 mm
Package weight (single piece)	0.025 kg